

FRONT AND REAR BUSHING APPLICATIONS

INTERNATIONAL - PETERBILT

| MFR. | SIDE BAR C/L TO C/L | SPRING WIDTH | BUSHING O.D. | | REAR SHACKLE (1 per side) | | FRONT ANCHOR (1 per truck) | | MAX. AXLE RATING | COMMENTS |
|--|---------------------------|-----------------|--------------|--------|------------------------------|-------------------|-------------------------------|-------------------|---------------------------------|--|
| | | | EYE | HANGAR | KIT | FIGURE P. 7-10 | KIT | FIGURE P. 7-10 | | |
| I N T E R N A T I O N A L | 4.00 | 4.00 | THD* | THD* | 994511 | 3 | - | - | 12,000 | 9600 Series - 1995 & Newer |
| | 3.50 | 4.00 | 1.25 | 1.25 | 994433 | 2 | - | - | 12,000 | Threaded side bar |
| | 3.50 | 3.00 | 1.50 | 1.50 | 994514 | 4 | - | - | 20,000 | School Bus |
| | 3.50 | 4.00 | 1.50 | 1.50 | 994416 | 2 | - | - | 20,000 | Threaded side bars |
| | 4.00 | 4.00 | 1.75 | 1.50 | 994501 | 4 | - | - | 20,000 | - |
| | 4.00 | 4.00 | 1.76 | 1.76 | 994502 | 4 | - | - | 20,000 | - |
| | 4.32 | 4.00 | 1.76 | THD* | 994403 | 3 | - | - | 12,000 | Except 4000 Series, 1982 & older |
| | 4.00 | 4.00 | 1.76 | THD* | 994405 | 3 | 994486 | 5 | 12,000 | Threaded side bars |
| | 4.00 | 4.00 | 1.84 | 1.84 | 994605 | - | - | - | - | - |
| | 3.25 | 4.00 | 1.76 | THD* | 994431 | 3 | 994486 | 5 | 12,000 | Except 5000 Series for 994486 |
| | 4.32 | 4.00 | 1.77 | 1.77 | 994415 | 4 | 994486 | 5 | 20,000 | - |
| | - | 4.00 | 1.50 | - | - | - | 994588 | 6 | 20,000 | - |
| | 3.50 | 4.00 | 1.25 | 1.50 | 994606 | 2 | - | - | 12,000 | 2000, 3000, 4000, 8000 models Threaded side bars |
| | 3.25 | 4.00 | 1.76 | THD* | 994607 | 3 | - | - | 12,000 | 8000, 9000 models. Threaded side bars. |
| | 3.50 | 4.00 | 1.50 | 1.50 | 994613 | 4 | - | - | 20,000 | 2 smooth bushings. |
| 4.00 | 4.00 | 1.84 | 1.84 | 994968 | 3 | - | - | 20,000 | 9000 models. 2 ribbed bushings. | |
| K E N W O R T H ** | 5.00 | 4.00 | 1.75 | 1.75 | 994426 | 4 | 994570 OR 994471 | 6 | 20,000 | Offset side bar – T2000 |
| | 4.00 | 4.00 | 1.75 | 1.75 | 994425 | 4 | 994471 OR 994570 | 6 | 20,000 | Older Conventional W900, uses 994425 if driver side aluminum hanger has been replaced with a steel hanger. Use 994427 or 994500 if aluminum. |
| | 4.00 | 4.00 | 1.75 | 1.75 | 994427 | 4 | 994471 OR 994570 | 6 | 20,000 | Offset side bar - New Conventional |
| | 4.00 | 4.00 | 1.75 | 1.75 | 994500 | 4 | - | - | 20,000 | Offset side bar - One threaded side bar, one thru hole side bar. Left side only. |
| | 4.00 | 4.00 | 1.75 | 1.75 | 994612 | 4 | - | - | 20,000 | Offset side bar - One threaded side bar, one thru hole side bar. Right side only. |
| M A C K | 4.00 | 3.50 | 1.76 | 1.76 | 994428 | 4 | - | - | 20,000 | CL model |
| | 4.00 | 3.44 | 1.87 | 1.88 | 994513 | 4 | 994512 | 6 | 20,000 | CH model |
| | 4.00 | 4.00 | 1.88 | 1.88 | 994429 | 4 | - | - | 20,000 | - |
| | 4.00 | 3.50 | 1.50 | 1.76 | 994587 | 4 | 994586 | 5 | 20,000 | RD & RB model |
| MAR- MON | 3.50 | 4.00 | 1.50 | 1.50 | 994401 | 4 | - | - | 20,000 | - |
| OTT- AWA | 4.00 | 4.00 | 1.37 | 1.50 | 994593 | 4 | - | - | 12,000 | - |
| P E T E R B I L T | 3.50 | 3.50 | 1.50 | 1.50 | 994400 | 4 | - | - | 20,000 | 59 conventional can only use this kit If equipped with 3.50" wide hanger bracket |
| | 3.50 | 4.00 | 1.50 | 1.50 | 994401 | 4 | 994434 | 6 | 20,000 | C.O.E. & Conventional |
| | 5.25 | 4.00 | 1.50 | 1.50 | 994408 | 4 | 994434 | 6 | 20,000 | Setback |
| | 3.50 | 4.00 | 1.50 | 1.50 | 994483 | 4 | - | - | 20,000 | 3.50 hanger width |
| | 5.00 STEEL | 4.00 | 1.50 | 1.50 | 994474 | 7 | 994434 | 6 | 20,000 | Peterbilt Air Ride – 1.50 Collar 3 smooth bushings. |
| | 4.61 | 4.00 | 1.50 | 1.50 | 994601 | 4 | - | - | 20,000 | 387 model |
| | 5.25 | 4.00 | 1.75 | 1.50 | 994610 | 4 | - | - | - | 387 model |
| | 3.50 | 4.00 | 1.75 | 1.50 | 994611 | 4 | - | - | - | 387 model |

* 1.375 Threaded Bushing: Replaces OE Threaded Pin

** For Kenworth Front Anchor Kits, 994570 is used to replace greaseless rubber mounted bushings. 994471 is used to replace greasable bushings.